





DESIGN <i>[Signature]</i>	DRAWN BY <i>[Signature]</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED <i>[Signature]</i>	APPROVED <i>[Signature]</i>	DRAWING NO. D2658	REV. D SHEET 1 OF 1
DATE 98.12.14		TITLE LUG BRACKET	SCALE 5:9
A	97.11.03	NEW ISSUE	
B	97.12.18	5.205 WAS 5.015, ADD TOOLING HOLE	
C	98.10.23	UPDATE MATERIAL (TSR A1114)	
D	98.12.14	REMOVE TOOLING HOLE (TSR A1040)	

RELEASED
98.12.14 DS



D2658 FLAT PATTERN
SYMMETRICAL ABOUT BOTH CENTRE-LINES (C)



D2658 BEND DETAIL

D2658 SHOULD BE BENT SO THAT IT IS WITHIN 0.010 OF THE OUTSIDE PROFILE OF THE D2600-1 EXTRUSION IN THE AREAS INDICATED 'X' ABOVE.

GENERAL NOTES

MATERIAL: ASTM A36/A366/A569/A570 OR AISI 1010-1025 STEEL 0.100 THICK (12 GAUGE)
MIN. ULTIMATE TENSILE STRENGTH = 42 ksi
MIN. YIELD TENSILE STRENGTH = 28 ksi

TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
ALL DIMENSIONS ARE IN INCHES